



Proof of RCM Compliance

Cert.No.: POC23050404

Date of issue: 5-May-2023

Certificate Holder: Wuxi Dpower electronic Co., Ltd.
Address: No.28 Xichang Road, Yanqiao Street, Huishan Distinct, Wuxi City,
214171 Jiangsu P.R. China

Product Description: Li-ion Battery Charger
Brand/Trade Name: Dpower
Model Number: DPLC177V59-M
Refer to model list

Electrical Ratings: Input: 110-240V~, 50/60Hz, 2.5A, Class II
Output: Refer to model list

AusRCM Compliance certifies that the Electrical/Electronic Article(s) as described above meets the requirements of the standard(s) listed below;

Compliance for: **Evidenced by:**

ACMA mandated
standards –eg.EMC

Test report and Declaration of Conformity
AS/NZS CISPR 14.1:2021

Electrical Safety
Standard(s):

Certificate of Conformity
AS/NZS 60335.2.29: 2017 including A1;
AS/NZS 60335.1: 2020 including A1
GMA-515173-EA
Date of Expire: 29-Apr-2028

EESS- National
Equipment Database
registration

Checked above model number(s) being registered as
LEVEL 3 product on
<https://equipment.erac.gov.au/Registration/EquipmentSearch.aspx?atn=public>

As of above, the Applicable Compliance mark shall be:




On behalf of AusRCM Compliance

Suite 206, 585 Little Collins Street, Melbourne ,VIC, 3000, Australia.



Proof of RCM Compliance

Cert.No.: POC23050404

Appendix -Model list

Model	Rating
DPLC177V59-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:58.8V , 3.0A
DPLC174V58-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:58.4V , 3.0A
DPLC166V55-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:54.8V , 3.0A
DPLC165V55-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:54.6V , 3.0A
DPLC153V51-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:51.1V , 3.0A
DPLC151V50-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:50.4V , 3.0A
DPLC150V50-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:50.2V , 3.0A
DPLC144V48-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:47.5V , 3.0A
DPLC168V42-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:42.0V , 3.0A
DPLC126V42-M	Input: 110-240V~, 50/60Hz, 2.5A, Class II Output:42.0V , 4.0A